

功能特点 Main Functions

- TDMA Mode With 2 Slots
- Integrated Heat Sink and Back Panel Fan
- Smart Detection Digital & Analog Signals in Single Channel
- Sharing A Channel With Multiple Groups
- Brightly LED Indication
- Automatic Voltage and Temperature Protection
- Support Third Party Diplexer Built-in



技术参数 Technical Specification

整机部分 GENERAL		发射部分 TRANSMITTER		接收部分 RECEIVER	
频率范围 Frequency Range	400-470MHz / 136-174MHz	射频功率 Output Power	25W	接收灵敏度 Sensitivity	0.25uV @ 12dB SINAD
信道容量 Channel Capacity	100	发射电流 Transmission Current	≤11A @ 13.8V	邻道选择性 Adjacent Channel Selectivity	60dB @ 12.5KHz / 70dB @ 25KHz
频率稳定性 Frequency Stability	±0.5ppm	待机电流 Standby Current	≤0.8A @ 13.8V	互调 Inter-modulation	≥60dB / ≥65dB
工作温度 Operating Temperature	-30 °C ~ +60 °C	调制方式 Modulation	11KΦF3E / 16KΦF3E	假信号响应 Spurious Response Anti-interference	≥70dB
工作电压 Operating Voltage	220V/110V(50Hz) AC±15%/13.8V DC±15%	调制失真 Modulation Distortion	<5%	音频响应 Audio Response	+1---3dB
尺寸(H*W*D) Dimension(H*W*D)	133mm x 483mm x 330mm	调频噪声 FM Noise	≥40dB @ 25KHz / ≥35dB @ 12.5khz	音频失真 Audio Distortion	<5%
重量 Weight	16kg	邻道功率 Adjacent Channel Power	≥60dB @ 12.5KHz / ≥70dB @ 255khz	调频噪声 FM Noise	≥45dB @ 25KHz / ≥40dB @ 12.5khz
		音频响应 Audio Response	+1---3dB		
		数字协议 DMR Protocol	ETSITS102 361-1,-2		



泉州市驰尔达电子通讯有限公司
 Quanzhou Chierda Electronic Telecom Co.,Ltd.
<http://www.fjhd.com>
www.chierda.com
 服务热线: 400-8090-768
 所有资料经过小心校对,以求准确。如有任何印刷错误或在翻译中可能产生之误差,本公司不承担因此产生之后果。

经销商