



## 4-Band Analog walkie talkie

(RX)64-108MHz (RX)108-136MHz

136-520MHz



- One click frequency matching
- 4-band transmission, 6-band reception
- Multiple frequency hopping groups
- Emergency alarm function
- IP67 waterproof
- Noise reduction function (optional)
- Low, medium, and high power switching
- Scan, mute, listen
- High definition Voice
- Dual frequency dual defense
- GPS/Beidou function

Note: Specifications may vary based on regional compliance requirements. The information provided reflects typical performance parameters and may be revised without prior notice. Product availability is subject to applicable local regulations.



### Product technical parameters

Analog dual band walkie-talkie

**ET-UV58**

#### Whole machine part

Power requirements	7.4V
Battery	2600mAh (3200mAh)
Dimensions	141*65*38mm(Without antenna)
Weight	195g(Without battery)
Intermodulation	65dB/60dB
Audio Distortion	≤5%
Audio output	<1W(16Ω)

#### General specification

Frequency range	Rx:64-108MHz(FM radio frequency band); 108-136MHz(AM aviation frequency band); 136-520MHz
Channel capacity	199
Receiving sensitivity	0.22μV/0.25μV 12dB SINAD
Signal Noise Ratio	-45dB/-40dB

#### Transmitting part

Output power	≤5W
Modulation Type	F3E
Maximum offset	≤5KHZ/≤2.5KHZ
Frequency stability	±2.5ppm
Channel spacing	12.5/25.0KHz

#### Use environment

Operating temperature	-20°C ~ +60°C
-----------------------	---------------

#### All Accessories



Host

Antenna

Back clip

Battery

Charger

sling

#### Scope of application



Fleet

Camp

Property security

Hotel

Construction site

warehouse

Guangzhou Etmy Technology Co., Ltd.